>> WICLINE 65 evo / 75 evo Classic design



Bevelled profile contours and overlapping sashes are characteristic for the aluminium door series WICSTYLE evo in a classic design. This design underlines a style which is often requested for residential architecture. Ideal for new building and for energetic renovations alike.



System test results / CE product pass in accordance with DIN EN 14351-1:2006+A1:2010

Air permeability:	Class 4
Watertightness:	E900
Resistance to wind load:	Class C5/B5
Acoustic performance:	$R_{w}(C; C_{tr}) = 47 (-1; -4) dB$
Operating forces:	Class 1
Load bearing capacity of safety devices:	Fulfilled
Mechanical strength:	Class 4
Repeated opening/closing:	Class 3 (20000 cycles)
Corrosion resistance of the fittings:	Class 5
Burglar resistance:	RC1N, RC2N, RC2, RC3
Quality assurance:	Certified according to ISO 9001:2008
Environmental management:	Certified according to ISO 14001

Technical performance:

Profile technology:

- High insulation multi-chamber system in symmetric design, quality assured thermal insulator connection, with 30° bevelled glazing rebates
- Patented corner and butt joint connection technology for high rigidity of frames and sashes
- Infill thickness up to 59 mm

Thermal insulation:

- U_f values: until 1.5 W/(m²K)
- U_w values: until 0.84 W/(m²K) with triple glazing

Sealing concept:

- Voluminous centre gasket with three
 - installation methods:
 - Circumferential centre gasket, avoiding joints in the corner areas
 - Formed corners, avoiding adhesive in the joints
 - Corner vulcanised frames

Hardware:

- Heavy duty system fittings with:
 - visible hinges, powder coating or anodisation in all colours
 - concealed hinges with integrated end position damping, opening angle max. 105°
- Sash weight:
 - Visible hinges: up to 100 kg
 - Concealed hinges: up to 100 kg
- Sash sizes (w x h): 1300 mm x 1700 mm
- Optionally with opening limiter in various executions

Additional options in classic design:

- Flush sash in classic design
- Overlapping sash and frame in classic design
- Fixed glazing
- Double casement window
- Crossbar profiles and glazing bars
- Integration frame for stick façades
- Fanlight
- Burglar resistance (see system tests)

Compatible with the door series WICSTYLE 65 evo and WICSTYLE 75 evo in Classic Design



